WECLIC SPC Technical Specifications

Property	Test standard	Specification / Result
Total thickness		6 mm (5 mm + 1 mm IXPE)
wear layer		0.5 mm (20 MIL)
Tile Size		Plank: 7" × 48" | Tile: 12" × 24"
Bevelled Edge		NO
Classification		
Reaction to fire	EN13501-1 EN ISO 11925-2 EN ISO 9239-1	Bfl – S1 Pass Pass
Resistance to Chemicals	EN 423; ASTM F925; ASTM F1344	Pass
Resistance to Light	EN 20105:B02 Method A; ASTM F1515	≥6
Wear resistance	EN 660-1/2; ASTM F510; ASTM D3384	Wear Group: T
Dimensional stability	EN 434; ASTM F2199	Pass (0.1%)
Acoustic Impact noise reduction	EN ISO 717-2 (ΔLw)	2 dB
Static electrical propensity		
Residual Indentation	EN 433; ASTM F1914; ASTM F970	Pass, 0.06 mm; Pass
Anti-slip property	EN 13893; ASTM F137	Class DS; Pass
VOC emission		
Phthalates		
Castor chair continuous use	EN 425	Pass

Product description

Providing and fixing Weclic SPC Click Flooring of VIBRANT FLOORS series. Regular plank size: 7 in × 48 in; regular tile size: 12 in × 24 in. Overall thickness: 6 mm (5 mm SPC + 1 mm IXPE); wear layer: 0.5 mm (20 MIL). Packing: 8 planks per box (18.69 sq. ft. per box) or 10 tiles per box (20 sq. ft. per box). The product is a rigid, water-resistant SPC flooring with an advanced click system. Install on a suitable, properly prepared subfloor in accordance with the manufacturer's installation guidance. Technical values and test results are as stated in the Weclic SPC brochure; characteristics not stated in the brochure are marked accordingly. Final shade and colour as approved by the architect.